

Pro 20 MP Fire Extinguisher

Part number 466206

Multipurpose use

Rechargeable

UL Rated 10-A:80-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Pro 20 MP unit is fitted with a pressure gauge that provides at-a-glance status, cylinder is manufactured from impact resistant steel and the valve assembly is all metal.


Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 18 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with mounting bracket (not supplied)
- Powder coated cylinder for corrosion protection
- U.S.C.G. approved bracket part number 292474

At a Glance

- Model Pro 20 MP
- Multipurpose Dry Chemical
- UL listed
- UL rated 10-A:80-B:C
- Supplied with wall hanger
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:



Pt # 466206 - 1 pack
UPC: 0-47871-66206-7
I2F - 20047871662061

Product Specification

Net agent weight (Average)	18 lb.
Unit weight (Average)	30 lb.
Diameter	7.0 inches
Height	21.6 inches
Discharge time	19-22 seconds
Discharge range	20 feet
Operating pressure	195 psi
Cylinder	Mild steel
Valve, handle, lever	Metal
Strap Bracket (not supplied)	U.S.C.G approved

Packaging Options



SHIPPED IN CARTON

Packaging dimensions (inches)

	Depth	Width	Height
Carton	7.5	7.5	21.75



Kidde Residential and Commercial Division
1016 Corporate Park Drive, Mebane, NC 27302
(800) 880-6788 www.Kidde.com