

5600 Series Mechanical Heat Detectors



Models Available

Single-circuit Models

| | |
|-------|--|
| 5601P | 135°F Fixed Temperature / Rate-of-Rise |
| 5602 | 194°F Fixed Temperature / Rate-of-Rise |
| 5603 | 135°F Fixed Temperature |
| 5604 | 194°F Fixed Temperature |

Dual-circuit Models

| | |
|------|--|
| 5621 | 135°F Fixed Temperature / Rate-of-Rise |
| 5622 | 194°F Fixed Temperature / Rate-of-Rise |
| 5623 | 135°F Fixed Temperature |
| 5624 | 194°F Fixed Temperature |



Product Overview

Multiple configurations available to satisfy a broad range of installations:

- Single- and dual-circuit models
- Fixed temp and combination fixed- temp/rate-of-rise
- 135°F or 194°F ratings.

Plain housing available for residential installations (model 5601P)

Easy to use terminal screws that provide a more positive wiring connection

A broader range of back box mounting options:

- Single gang
- 3.5" and 4" Octagonal
- 4" square with square to round plaster ring

Reversible mounting bracket for flush and surface mount installations

System Sensor's 5600 series mechanical heat detectors offer a low-cost means for property protection against fire, and for non-life-safety installations where smoke detectors are inappropriate.

Multiple configurations. The 5600 series offers a full-line of configurations to accommodate a broad range of applications. Both single- and dual-circuit models are offered, each available for low- and high-temperature ratings with either fixed temperature or combination fixed temperature/rate-of-rise (ROR) activation. The ROR element of the fixed/ROR models is restorable, to accommodate field-testing the unit.

Installation flexibility. To satisfy a variety of installations, the 5600 series easily mounts to single-gang and octagonal back boxes. These models also accommodate four-square back boxes, when used with a square to round plaster ring. The mounting bracket is reversible to allow for flush- and surface-mount back box installations.

Visual identification. The 5600 series provides clear markings on the exterior of the unit to ensure that the proper detector is being used. Alphanumeric characters identify the activation method, as well as the temperature rating, in degrees Fahrenheit and Celsius. Fixed temperature models are identified "FX", while combination fixed/rate-of-rise units are marked "FX/ROR". The 5600 series also provides a post-activation indicator in the form of a collector. Once the detector has been activated, the collector drops from the unit, to easily identify the specific unit in alarm.



Engineering Specification

Mechanical heat detector shall be a System Sensor 5600 series model number _____, listed to Underwriters Laboratories UL 521 for Heat Detectors for Fire Protective Signaling Systems. The detector shall be either a single-circuit or a dual-circuit type, normally open. The detector shall be rated for activation at either 135°F (57°C) or 194°F (90°C), and shall activate by means of a fixed temperature thermal sensor, or a combination fixed temperature/rate-of-rise thermal sensor. The rate-of-rise element shall be activated by a rapid rise in temperature, approximately 15°F (8.3°C) per minute. The detector shall include a reversible mounting bracket for mounting to 3½-inch and 4-inch octagonal, single gang, and 4-inch square back boxes with a square to round plaster ring. Wiring connections shall be made by means of SEMS screws that shall accommodate 14-22AWG wire. The detector shall contain alphanumeric markings on the exterior of the housing to identify its temperature rating and activation method. The rate-of-rise element of combination fixed temperature/rate-of-rise models shall be restorable, to allow for field-testing. The detectors shall include an external collector that shall drop upon activation to identify the unit in alarm.

Electrical Specifications

Operating Voltage / Contact Ratings

6 – 125VAC / 3A
 6 – 28VDC / 1A
 125VDC / 0.3A
 250VDC / 0.1A

Physical Specifications

Maximum Installation Temperature

5601P, 5603, 5621, and 5623: 100°F (38°C)
 5602, 5604, 5622, and 5624: 150°F (65.6°C)

Alarm Temperature

5601P, 5603, 5621, and 5623: 135°F (57°C)
 5602, 5604, 5622, and 5624: 194°F (90°C)

Rate-of-Rise Threshold

15°F (8.3°C) rise per minute
 (models 5601P, 5602, 5621, and 5622 only)

Operating Humidity Range

5 to 95% RH non-condensing

Input Terminals

14–22 AWG

Mounting

3½-inch octagonal back box
 4-inch octagonal back box
 Single gang back box
 4-inch square back box with a square to round plaster ring

Dimensions with mounting bracket

Diameter: 4.57 inches (11.6cm)
 Height: 1.69 inches (4.3cm)


Weight

6 oz. (170 grams)


Ordering Information

| Model | Circuit | Identification Method on Exterior | Temperature Rating | Activation | UL Protected Spacing – 10 Foot Ceiling* |
|-------|---------|-----------------------------------|--------------------|----------------------------------|---|
| 5601P | Single | None | 135°F (57°C) | Fixed Temperature / Rate-of-Rise | 50 feet × 50 feet (15.24m × 15.2m) |
| 5602 | Single | Lettering | 194°F (90°C) | Fixed Temperature / Rate-of-Rise | 50 feet × 50 feet (15.24m × 15.2m) |
| 5603 | Single | Lettering | 135°F (57°C) | Fixed Temperature | 25 feet × 25 feet (7.62m × 7.62m) |
| 5604 | Single | Lettering | 194°F (90°C) | Fixed Temperature | 25 feet × 25 feet (7.62m × 7.62m) |
| 5621 | Dual | Lettering | 135°F (57°C) | Fixed Temperature / Rate-of-Rise | 50 feet × 50 feet (15.24m × 15.2m) |
| 5622 | Dual | Lettering | 194°F (90°C) | Fixed Temperature / Rate-of-Rise | 50 feet × 50 feet (15.24m × 15.2m) |
| 5623 | Dual | Lettering | 135°F (57°C) | Fixed Temperature | 25 feet × 25 feet (7.62m × 7.62m) |
| 5624 | Dual | Lettering | 194°F (90°C) | Fixed Temperature | 25 feet × 25 feet (7.62m × 7.62m) |


*NOTE: Refer to NFPA72 guidelines for spacing reductions when ceiling heights exceed 10 feet.




5601P




5602, 5622



5603, 5623



5604, 5624



5621

System Sensor Sales and Service

System Sensor Headquarters

3825 Ohio Avenue
 St. Charles, IL 60174
 Ph: 800/SENSOR2
 Fx: 630/377-6495
 www.systemsensor.com

System Sensor Canada

Ph: 905.812.0767
 Fx: 905.812.0771

System Sensor Europe

Ph: 44.1403.891920
 Fx: 44.1403.891921

System Sensor in China

Ph: 86.29.8832.0119
 Fx: 86.29.8832.5119

System Sensor in Singapore

Ph: 65.6273.2230
 Fx: 65.6273.2610

System Sensor – Far East

Ph: 85.22.191.9003
 Fx: 85.22.736.6580

System Sensor – Australia

Ph: 613.54.281.142
 Fx: 613.54.281.172

System Sensor – India

Ph: 91.124.237.1770 x.2700
 Fx: 91.124.237.3118

System Sensor – Russia

Ph: 70.95.937.7982
 Fx: 70.95.937.7983