



Mini-Horns

The SpectrAlert® Advance series of mini-horn sounders are designed to simplify installations to provide primary and secondary signaling for fire and security applications.



SPECTRAlert
ADVANCE
from System Sensor

Features

- 12 and 24V operation
- High and low volume settings
- Temporal and non-temporal tones
- Mounts to single gang back box
- Compatible with MDL sync module
- Mechanically and electrically compatible with PA400 series Mini-Alert™ sounders

The MHR and MHW mini-horns operate at 12 and 24 volts and are ideal for hotel, motel or residential fire system applications, where a smaller notification device is desired. The mini-horns offer high and low volume settings, and temporal or non-temporal tones. The horns can be mounted to single gang back boxes for aesthetically sensitive applications. Synchronization is also provided when using the MDL module.

The MHR and MHW mini-horns can operate between 32 and 120 degrees Fahrenheit from a regulated DC or full-wave rectified, unfiltered power supply. They are listed to Underwriter's Laboratories Standard UL 464 for fire protective signaling systems.

Agency Listings



S4011



3028007



MEA7-07-E



7135-1653:196

SpectrAlert® Advance Mini-Horn Specifications

Architectural/Engineering Specifications

Mini-horns shall be a System Sensor Model MHR or MHW capable of operating at nominal 12 or 24VDC and shall mount to a single gang back box. Mini-horn shall be listed to Underwriter's Laboratories Standard UL464 for fire protective signaling systems. Mini-horns shall operate between 32 and 120 degrees Fahrenheit from a regulated DC, or full-wave rectified, unfiltered power supply. When used with the Sync-Circuit™ Module, 12-volt rated notification appliance circuit outputs shall operate between nine and 17.5 volts; 24-volt rated notification appliance circuit outputs shall operate between 17 and 33 volts.

Physical Specifications

Dimensions	4.6"L x 2.9"W x .45"D
Weight	2.67 oz.
Operating Temperature Range	32°F to 120°F (0°C to 49°C)
Mounting	Surface: single-gang back box Flush: 4" x 4" BBD deep back box (2¾" deep)

Electrical Specifications

Input Terminals	12 to 18 AWG
Nominal Voltage	Regulated 12DC/FWR or regulated 24DC/FWR
Operating Voltage	8-33
Operating Voltage with MDL	9-33

UL Sound Output and Current Draw Data

Sounder Output (dBA)

Switch Setting	Pattern	Output Level	8-17.5 VDC	8-17.5 VFWR	Nominal 12 VDC	Nominal 12 VFWR	16-33 VDC	16-33 VFWR
1	Temporal	High	68	67	71	70	78	76
2	Temporal	Low	66	65	69	68	76	75
3	Non-temporal	High	72	71	75	74	80	79
4	Non-temporal	Low	70	69	73	72	78	77

Sounder Current Draw (mA RMS)

Switch Position	Sound Pattern	Volume	8-17.5 Volts		16-33 Volts	
			DC	FWR	DC	FWR
1	Temporal	High	12	10	17	15
2	Temporal	Low	10	9	14	13
3	Non-temporal	High	22	17	29	25
4	Non-temporal	Low	17	13	21	19

Ordering Information

Part No.	Description
MHR	Mini-Horn, Red
MHW	Mini-Horn, White

