

STI HEATER KIT

To Protect Costly Electronic Components in Frigid Areas

These easy to install kits are the answer for protecting expensive electronic units that must be installed in low temperature areas, indoors or outdoors. They operate with enclosed covers. In addition to assuring continued operation of protected units, they also keep LCD's from becoming sluggish and help them stay visible.

Two Basic Systems Available

The 12-volt system (STI-6580) incorporates a 12-volt transformer and is rated at 25 watts. The 24-volt system (STI-6583) is designed to get its power directly from a remote power supply (other than the fire panel) or CCTV power source. It is rated at 8 watts. Both systems include a foil heater pad with adhesive backing and a thermostat.



Features

- Allows critical electronic components to operate at low temperatures.
- Self-adhesive heater pad.
- Keeps control panels warm when mounted in a protective cover or enclosed space. Results may vary based on installation and enclosure used.
- Temperature controlled.
- Thermostat active 23°F to 41°F (-5°C to 5°C).
- Both 12-volt and 24-volt models available.
- Can be mounted inside control panels to keep batteries and electronics operational.
- Keeps LCD's from becoming sluggish and helps them stay visible at freezing temperatures.
- Easy to install and highly effective.
- One (1) year warranty from the date of original purchase.



Safety Technology International, Inc.

2306 Airport Road • Waterford, Michigan 48327-1209

Phone: 248-673-9898 • Fax: 248-673-1246 • Toll Free: 800-888-4784 • E-mail: info@sti-usa.com • Web: www.sti-usa.com

Europe Branch Office • Unit 49G Pipers Road • Park Farm Industrial Estate • Redditch • Worcestershire • B98 0HU • England

Tel: 44 (0) 1527 520 999 • Fax: 44 (0) 1527 501 999 • Freephone: 0800 085 1678 (UK only) • E-mail: info@sti-europe.com • Web: www.sti-europe.com

STI HEATER KIT

Dimensions and Technical Information

Models Available

STI-6580 12 volt heater Kit
STI-6583 24 volt heater Kit

SPECIFICATIONS

Heater Pad Size	4" x 5 1/2"
Thermostat Size	3/4" x 1/4" x 3/16"
Thermostat Active	23°F to 41°F (-5°C to 5°C) Creep action thermostat
STI-6580 power	12 Volt 25 Watts (2.25 amp) AC or DC 40 VA 12 VAC Power Supply Included
STI-6583 power	24 Volt 12 Watts (.5 amp) AC or DC Power Supply Not Included

Note

Keeps control panels warm when mounted in a protective cover or enclosed space. Results may vary based on installation and enclosure used.

