

TEMP°ALERT®

PROTECT PROPERTY FROM THE ADVERSE EFFECTS OF TEMPERATURE EXTREMES



TA-1 Temperature Monitor

- Monitors -30 to +130° F (-34 to +54° C)
- Adjustable high and low alarm set points
- Requires no power to operate
- Connects to any hardwire or wireless alarm system
- **Not for use in freezer or cooler monitoring, instead use an EnviroAlert® with a remote probe**

SPECIFICATIONS

TA-1 TEMP°ALERT®

| SPECIFICATION | VALUE |
|---|--|
| Low Limit Adjust Range | -30 to +120° F (-34 to +49° C) |
| High Limit Adjust Range | -20 to +130° F (-29 to +54° C) |
| Minimum Span (Rec. dist. between high and low set pts.) | 10° F (5.6° C) |
| Temp Accuracy | ±3° F (±1.7° C) |
| Temp Response Time | TC= 14 minutes |
| Temp Sensing Element | Bimetallic coil |
| Outputs (Not for high voltage use) | Gold plated N/O Dry Contacts |
| Contact Output Rating | 12VDC @ 50mA |
| Control Box Material | ABS |
| Weight | 6 ounces (170 g) |
| Dimensions | 6.25" x 3.75" x 1" (15.9 cm x 9.5 cm x 2.5 cm) |
| Mounting | Key slot |



1950 Excel Drive
Mankato, MN 56001
1-800-635-4269
In MN: 507-625-7231
FAX: 507-387-2488
www.winlandsecurity.com

